

AF1206A



Characteristics

External Dimensions (W x D x H) cm 95 x 65,5 x 113**Structure and Insulation** stainless steel inside and outside**Height adjustable Feet****Kind of ice** flakes**Motor cooling** air**Production Kg/24h (up to)** 200**Bin capacity (kg)** 60**Weight** kg 77

Technical data

Details

- Refrigerant type: R134A CFC free
- Mains Voltage: 230V/1/50Hz
- Power Consumption: 11,2 kW/h
- Water consumption l/h: 6,5
- Electrical consumption: 760W
- Fuse (A): 10
- Cooling Capacity Btuh/W: 6480
- Water temperature min/max: 5°C-35°C
- Pressure min/max: 1 bar/5 bar
- Noise level < 66 dB
- Ambient Temperature: +10/+32 °C; humidity 60%

In accordance with 2014/30/CE, 2014/35/CE and following modifications**Package** Strong Cardboard on wooden pallet**note** Available also water cooled

Accessories

Kit for Demineralized Water

60 Hz Frequency

115 V

Wooden crate Package

FIOCCHETTI SCIENTIFIC S.R.L.

Via Panagulis, 48 - 42045 Luzzara (RE) Italy
Tel. +39 0522 976232- Fax +39 0522 976028
info@fiocchetti.it - www.fiocchetti.it
P.I.00934960352
Registro A.E.E. IT8020000002833